

# SNBC

Extraordinary Value!

# BTP-M300

## Series Impact Receipt Printer



Contains Everything Necessary – Including the Communication Cables – in the Carton

### Preferred for POS, Bar, Kitchen, and Data-Logging Printer Applications

The SNBC BTP-M300 produces clear, precise and archive-quality documents. It is ideal for requisitions and receipts including coupons, rebates and special offers. Featuring trouble free drop-and-print paper loading, the extraordinarily reliable M300 provides paper “pull” technology for jam-free operation and best-in-class cutter performance. The internal power supply eliminates unsightly and messy cords and bricks.

- Choose a USB or Ethernet On-Board Interface
- Serial, Parallel, USB, Ethernet, Bluetooth and WiFi Interfaces Options
- Cutter Rated for 1,800,000 Cuts (BTP-M300)
- Energy Star Certified
- SDK Available for iOS and Android Operating Systems

#### BTP-M300 – Auto Cutter



#### BTP-M300D – Manual Tear



# BTP-M300 Series Impact Receipt Printer



**Drop and Print Paper Loading with Built-In Paper Width Selector**



**Optional Audio/Visual Print Messenger**



**Built-In Wall Mount Capability**



**Concealed, Yet Easy to Access Power Supply – Dual Interface Boards Allow a Variety of Configurations**

## Features

Proven impact printing technology preferred for POS kitchen printer and archivable receipt applications.

- Choose from USB or Ethernet on Board
- Serial, Parallel, Ethernet, USB, Bluetooth and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Most Other SNBC Printers
- Auto-Cutter with **Selectable** Full or Partial Cut (Tear Bar also Included – BTP-M300)
- Two-Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Fast 4.7 Lines per Second Print Speed
- Drop and Print Paper Loading
- Stores and Prints Logo Images
- Built-In Wall Mount Capability
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches
- Includes Starter Paper Roll, Paper Width Selector, Appropriate Communications Cables, Power Cord, Power Switch Cover, Ribbon and a CD-ROM with Drivers, Utilities and User's Manual

## Optional Devices / Upgrades

Modify or upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet, Bluetooth and Wireless WiFi Interface Boards are User Interchangeable
- USB+Cash Drawer Port or Ethernet+Cash Drawer Port
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed

## Ports and Connectivity



- 1 USB+Cash Drawer or Ethernet+Cash Drawer Versions Available
- 2 Choice of Serial (Shown), Parallel, USB, Ethernet, Bluetooth or Wireless WiFi Interface Boards Available

Standard configurations shown. Create other configurations by purchasing interface boards separately.

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

## Specifications

<b>Max. Print Speed:</b>	4.7 Lines per Second / 19.6mm per Second
<b>Printing Method:</b>	Impact
<b>Characters Per Line – Font A:</b>	33 / 35
<b>Font B:</b>	40 / 42
<b>Characters Size – Font A:</b>	9 x 9
<b>Font B:</b>	7 x 9
<b>Paper Roll Type – Width:</b>	80 / 76 / 69.5 / 57.5mm ± 0.5mm
<b>Maximum Diameter:</b>	83mm
<b>Paper Thickness:</b>	0.06mm ~ 0.085mm
<b>2-Ply Paper Thickness:</b>	0.05mm ~ 0.08mm Total ≤ 0.14mm
<b>Auto Paper Cutting Method:</b>	Auto-Cutter with <b>Selectable</b> Full or Partial Cut
<b>Inking Supply:</b>	ERC-38 Ribbon Cartridge (Black/Red)
<b>Reliability – MTBF:</b>	180,000 Hours
<b>MCBF:</b>	18,000,000 Lines
<b>Printhead Life:</b>	150,000,000 Characters
<b>Cutter Life:</b>	1,800,000 Cuts (BTP-M300)
<b>Character Set – Alphanumeric:</b>	95
<b>International:</b>	37
<b>Graphic:</b>	128 x 12 Page / Traditional/Simplified Chinese / Thai / Japanese
<b>Interpreter:</b>	ESC/POST™
<b>Interface – Board 1:</b>	USB+Cash Drawer or Ethernet+Cash Drawer
<b>Board 2:</b>	Serial / Parallel / USB / Bluetooth / WiFi / Ethernet
<b>Drivers – 32 bit:</b>	POSReady 2009 / 2000 Server / 2000 Prof. / XP Home
<b>32 and 64 bit:</b>	Win 8 / Win 7 / Server 2008 / Server 2003 / XP Prof. / Vista
<b>Other:</b>	Linux / OPOS / BYJavaPOS Windows / BYJavaPOS Linux
<b>Software Development Kit:</b>	iOS / Android
<b>Drawer Port:</b>	Up to 2 Drawers (+24VDC) / Supports Drawer Compulsion
<b>Data Buffer– Rec. Buffer RAM:</b>	8 KB RAM
<b>RAM Bitmap:</b>	8 KB
<b>Flash Bitmap:</b>	128 KB
<b>Power Supply:</b>	24V DC ± 5% Internal Adapter Included
<b>Current/Power Usage:</b>	1.5A / 36W
<b>Operating Temperature:</b>	40° ~ 114°F (5° ~ 45°C)
<b>Operating Humidity:</b>	20% ~ 90% RH (Non-Condensing)
<b>Dimensions:</b>	6-1/4"W x 6"H x 9-1/2"D
<b>Shipping Weight:</b>	9.0 lbs. (Each Unit) / 40 lbs. (Master Carton 4)
<b>Safety and EMI:</b>	FCC / RoHS



or