

SNBC

Extraordinary
Value!

BTP-R880NPV



**Fastest, Most Reliable and Versatile
POS Printer**



**Includes Standard USB, Serial and
Ethernet Interfaces**

SNBC's most advanced POS printer, the BTP-R880NPV equals or exceeds the specifications of the market's most respected printers without straining your budget.

- Triple Interface Standard – USB, Serial and Ethernet
- Blazing Fast 310mm/Second Print Speed
- Optional Parallel and WiFi Interface Boards
- Programmable Paper Saving Options
- No Dip Switches – Intuitive Keypad Programming
- Supports Windows® and Linux® Operating Systems
- SDK Available for Windows, iOS and Android

Contains Everything Necessary – Including
the Serial and USB Communication Cables
– in the Carton



BTP-R880NPV Thermal Receipt Printer



Drop and Print Paper Loading with an Adjustable Paper Width Selector



Liquid Guard Built Into the Cabinet Design



Built-In Wall Mount Capability and Optional Audio/Visual Print Messenger



Optional Spill Cover

Features

A low-cost high quality thermal receipt printer ideal for rugged environments.

- Triple Interface Standard – Serial, USB and Ethernet
- Parallel or Wireless Interface Boards Available
- Use the Same Interface Boards as Other SNBC Printers
- Energy Star Certification
- Programmable Paper Saving Options
- Adjustable Internal Buzzer Volume
- Auto-Cutter – **Selectable** Full or Partial Cut
- Cutter Life of Two Million Cuts
- Drop and Print Paper Loading
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- Everything Necessary is in the Carton –
- Includes Starter Paper Roll, External Power Adaptor and Cord, Paper Width Selector, Power Switch Cover, Serial and USB Cables, Wall Mount Kit and CD-ROM with Drivers, Utilities and User's Manual


Optional Devices / Upgrades

Modify or upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet, Serial+Ethernet and Wireless Interface Boards Are User Changeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Power Supply Cover
- Spill Cover

Ports and Connectivity

- A** DC 24V Power-In
- B** Cash Drawer Port
- C** USB Port
- D** Serial Port
- E** Ethernet Port
- F** Cable Management Clip



Specifications

Max. Print Speed –	Mono:	310mm per Second
	Grayscale:	150mm per Second
	Two-Color:	120mm per Second
Printing Method:	Direct Thermal	
Resolution:	203 DPI x 180 DPI	
Characters Per Line –	Font A:	53 (80mm) / 38 (58mm)
	Font B:	71 (80mm) / 51 (58mm)
Characters Size –	Font A:	12 x 24
	Font B:	9 x 17
Paper Roll Type –	Width:	57.5mm / 69.5mm / 76mm / 80mm / 82.5mm
	Maximum Diameter:	83mm
	Paper Thickness:	0.06mm ~ 0.1mm
Auto Paper Cutting Method:	Auto-Cutter with Selectable Full or Partial Cut	
Reliability –	MTBF:	360,000 Hours
	MCBF:	70,000,000 Lines
	Printhead Life:	150 Km
	Cutter Life:	2,000,000 Cuts
Character Set –	Alphanumeric:	95
	International:	13
	Code Pages:	56
Bar Code –	1D:	UPC-A / UPC-E / EAN8 / EAN13 / Code39 / Code93 / CODE128 / CODABAR / ITF
	2D:	PDF417 / QR Code / Maxicode / GS1-DataBar
Interpreter:	ESC/POST™	
Interface:	USB+Serial+Ethernet	
Drivers –	32 bit:	Windows XP Prof. / XP Home Edition / 2000 Server / 2000 Professional / POSReady 2009
	64 bit:	Windows XP / Server 2012
	32 and 64 bit:	Windows 10 / Windows 8 / Windows 7 / Server 2008 / Server 2003 / Vista
	Other:	Linux / OPOS / BYJavaPOS Windows / BYJavaPOS Linux
	Software Development Kit:	Windows / iOS / Android
Drawer Port:	Up to 2 Drawers (+24VDC) / Drawer Compulsion	
Data Buffer –Receive Buffer RAM:	64 KB	
	RAM Bitmap:	128 KB
	Flash Bitmap:	512 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included	
Current/Power Usage:	2.5A / 60W	
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)	
Operating Humidity:	20% ~ 90% RH (Non-Condensing)	
Dimensions:	5-3/4"W x 5-5/16"H x 7-5/8"D	
Shipping Weight:	6.64 lbs. (Each Unit) / 28.94 lbs. (Master Carton of 4)	
Safety and EMI:	FCC / RoHS	

Imported and Distributed by CRS Inc., Saint Paul, Minnesota • 1-800-333-4949 • www.crs-usa.com

All product and company names are trademarks, service marks or registered trademarks of their respective owners.

All features and specifications are subject to change without notice.

© 2017, Printed in U.S.A.

LIT-311

SNBC