



Cafeterias / Table Service / Quick Service



Tobacco Stores / Liquor Stores



Bars / Ice Cream Parlors / Restaurants



Dusty Environments Like Pizza and Bakeries



Hardware, Paint or General Retail Stores

Stylish POS Terminal with True Flat Touch Screen



The SPT-S260 includes both projected capacitive touch and a solid state drive. A true flat touch panel provides superior spill and dust resistance that ensures optimum performance in harsh retail and food service environments. The LED backlight ensures long display life and significant energy savings.

- Braswell Intel Celeron N3160 Quad Core Processor
- Slim Display, Sleek Chassis and Small Footprint Design
- Projected Capacitive Touch (PCT) – PCT is Inherently Faster, More Reliable and Robust
- Solid State Drive for Optimum Performance and Reliability
- Energy Efficient and Low Heat Generation Architecture
- Fanless Operation – No Problematic Ventilation Holes
- Meets IP55 Standards for Exposure to Dust – Water Proof Front Panel
- Superior Serviceability and Easy Installation
- Microsoft Azure Certified



SPT-S260 Touch Screen Terminal



Sleek and Stylish Cabinet Design



Optional Integrated 9.7" and 15" Rear LCD Customer Displays



Optional Integrated Rear VFD Customer Display



Easy Access to Solid State Drive

Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 15" or 9.7" LCD Customer Displays
- Integrated Fingerprint Reader
- WiFi Module
- Wall Mount Bracket with Standard VESA Configuration

Applications

The attractive, powerful SPT-S260 is ideal for demanding applications including table service, retail scanning and many more like these:

- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service Restaurant
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video
- Table Service Restaurant
- Training
- Unattended Workstations

Connectivity

- A** COM2 (Powered)
- B** COM1 (Powered)
- C** Line Out (Audio)
- D** LAN
- E** USB (2)
- F** COM 3 (Powered)
- G** USB (2)
- H** VGA
- I** DC In (Power)
- J** DC Out (For Rear LCD)
- K** Drawer Voltage Selector Switch
- L** Cash Drawer

Specifications

Processor:	Braswell Intel Celeron N3160 (Maximum 2.24GHz)
Cores / Threads:	Quad Core / 4 Threads
Cache Memory:	2MB
Display LCD:	True Flat 15" LCD with LED Backlighting
Resolution:	1024 x 768
Brightness:	Adjustable Up to 250 cd/m2
Integrated Speakers:	Integrated 2 Watt Speakers
Chipset (PCH):	System on Chip
Touch – Panel:	Projected Capacitive Touch
Reliability:	Over 100 Million Touches
MCR:	Integrated USB Interface Triple Track MCR
Storage:	128GB 2.5" Solid State Drive
RAM Memory (1 Slot):	4GB SODIMM DDR3L (1600MHz) Expandable To 8GB
Video Memory:	Shared System Memory Up to 1.7GB (Windows 7)
Serial Ports:	COM1, COM2 = DB9M With Pin 9 (0V/+5V/+12V) COM3 = RJ45 Pin 1 (0V/+5V/+12V) Voltage Selectable By BIOS
USB Ports:	6 – 2 V2.0, 2 V3.0 (Rear I/O) / 2 V2.0 (Side I/O)
Cash Drawer Port:	RJ11, 12V or 24V Selectable By Switch (Maximum 2 Drawers – Supports Drawer Compulsion)
LAN Port:	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111G
VGA Port:	One DB15F Display Port For Second LCD (Maximum Resolution 1920 x 1200)
Audio Port:	One Line-Out
Mic Port:	Not Applicable
Power Supply:	60W, 12V/5A External Power Adaptor 100-240V 50-60Hz
Current / Power Usage:	0.18A / 21.6W
Operating Temperature:	32° F to 95° F (0° C to 35° C)
Compatible O/S:	POSReady 7 / Windows 7 Professional / Windows 10 Professional / Windows 10 IoT Enterprise LTSB
Dimensions – Base:	8-1/2"W x 1-1/4"H x 10"D
Unit:	14-7/8"W x 14-1/4"H x 10-3/8"D
Shipping Carton:	20-3/8"W x 13-1/2"H x 19"D
Weight – Unit:	13.22 lbs.
Shipping Carton:	18.79 lbs.
Safety and EMI:	FCC, NRTL, RoHS

